

Beech ¹² inches in diameter S 38° W 36 lks dist
 Beech 10 " " " N 18° W 58 " "

Corners made and lines run in Section
 No 10 T 7 R 1 E

Length of line from the N W
 corner of Section 10 to the northern $\frac{1}{2}$ mile
 post of the same 169 Poles & 3' lks

New witness tree and corner made equal
 distant between the Southern $\frac{1}{2}$ mile post
 and the S W corner of the same
 Poplar 30 inches in diameter N 6° W 21 links distant

+ corner at the N. E. corner of Section No 9 T 7 R 1 E
 Beech 10 inches in diameter S 69° W 16 lks distant
 Oak 15 " " " S 77° E 19 " "

Section 10 T 7 R 1 E Length of the line
 north of the center 164 Poles & 7 links

Length of line west of center 161 Poles and 20 lks

corner 80 Poles 22 $\frac{1}{2}$ links west of the center
 Beech 10 inches in diameter and corner tree
 Robert Centright and Milton Strouss chain
 bearers sworn this may 12th 1856

James W Spencer
 M C Surveyor

Nov 20th A. D 1836

+ Ran the following lines
 and made the following corners in Section
 11 Township No 10 north of Range No 1 East
 for Eben Newton of Ohio

Beginning at the
 eastern $\frac{1}{2}$ mile post of said section witness
 trees Sugar 6 inches in diameter N 32° E 6 lks dist

Sugar 5 " " " S 31 W 19 " "

Then S 83° W 160 Poles to a stone witness
 tree Beech 18 inches in diameter S 74° E 26 $\frac{1}{2}$ lks dist

Maple 20 " " " S 13° E 60 " "

Then S 5° E 170 Poles to a stone witness
 Poplar 20 inches in diameter S 26° E 20 lks dist

Beech 10 " " " N 43° W 40 " "

This last named corner is the Southern